

Sparkweld ENGINEERING

DUAL PULSE C.D. WELDER

Series :DPCD 600



TENCHNICAL SPECIFICATIONS

MIN. & MAX. OUTPUT	:	5 - 600 WS
MIN. & MAX. PULSE WIDTH	:	3 - 50 msec.
MIN. & MAX. PULSE HIGHT	:	1.5 V – 18 V
PEAK CURRENT OUTPUT	:	(With External cabling 35 sq.mm x 4 ft.) 10,000 Amps.
	:	(With External cabling 20 sq.mm x 6 ft.) 8,500 Amps.
	:	(With External cabling 8 sq.mm x 6 ft.) 4,500 Amps.
INPUT SUPPLY :		230V / 50 Hz / 10 Amp.
DIMENSIONS (WxHxL) :		400X305X365
WEIGHT :		24 Kgs.

Sparkweld ENGINEERING

Manufacturer of Stud Welding Equipments

OFF. : UNIT NO. 62, FIRST FLOOR, JAGAT SATGURU INDUSTRIAL ESTATE, GOREGAON (E),
MUMBAI – 400 063.

• E-mail : sparkweldengg@hotmail.com • www.sparkweld.net
• Phone : 91-022-2927 1548/49 • Fax : 91-022-2927 6740 • Mobile : +919820877054